

DAMPFIX IMMERSED POWDER

Revision Number 2

Revision date 13-Dec-2021 Supersedes Date: 09-Oct-2016

Cupo. Couco Dato. 00 000 2010

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name DAMPFIX IMMERSED POWDER

Product Code(s) 30840501 30840501

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Waterproofing Sealers

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)

Label elements

Corrosion



Australia - EN Page 1/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

Signal word

Danger

Hazard statements

H315 - Causes skin irritation

H318 - Causes serious eye damage

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

IF ON SKIN: Wash with plenty of water and soap

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

Other hazards which do not result in classification

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system.

Repeated exposure may cause skin dryness or cracking.

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	10 - <30
Sulfuric acid, aluminum salt (3:2)	10043-01-3	< 1%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

Australia - EN Page 2/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Causes serious eye damage. Irritating to skin. Inhalation of dust in

high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

Revision date 13-Dec-2021

when kneeling in wet cement even when wearing trousers.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products Carbon oxides. Sulfur oxides. Silicon dioxide.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containmentCover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry.

Australia - EN Page 3/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

Revision date 13-Dec-2021

up spilled material and place in suitable container. Avoid generating dust.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or

clothing. Use personal protection equipment. Take off contaminated clothing and wash

before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	10 mg/m³ TWA
Sulfuric acid, aluminum salt (3:2) 10043-01-3	2 mg/m³ TWA

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Recommended filter type:. Wear a respirator conforming to EN 140 with Type P2/P3

filter or better.

Environmental exposure controls No information available.

Australia - EN Page 4/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical stateSolidAppearancePowderColorGrayOdorOdorless

Odor threshold No information available

Property Values Remarks • Method

pH No data available
pH (as aqueous solution) No data available
Melting point / freezing point Not applicable .

Initial boiling point and boiling Not applicable .

range

Flash point Not applicable .
Evaporation rate Not applicable .
Flammability No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableRelative vapor densityNo data available

Relative density 1.25

Water solubility Insoluble in water Cement based

products react and solidify in contact

with water

Solubility(ies)

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity

Dynamic viscosity

No data available
No data available
Not applicable .

Not applicable .

Explosive propertiesNo information available **Oxidizing properties**No information available

Other information

Softening Point Not relevant

Solid content (%) No information available Density No information available

VOC Content (%) 1 g/L SCAQMD Method 304-91

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under recommended storage conditions. Keep away from Incompatible materials.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

Australia - EN Page 5/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Product cures with moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Hazardous decomposition products

Hazardous decomposition Carbon oxides. Nitrogen oxides (NOx).

products

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, portland, chemicals	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
(Chromium VI reduced)			-
Sulfuric acid, aluminum salt	>2000 mg/kg (Rattus)	> 5000 mg/kg (Rabbit)	-
(3:2)			

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

Australia - EN Page 6/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity No information available.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity No information available.

STOT - single exposureBased on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Not applicable.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sulfuric acid, aluminum	-	LC50 96 h = 100 mg/L	-	EC50: =136mg/L
salt (3:2)		(Carassius auratus)		(15min, Daphnia magna)
10043-01-3				

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Mobility

Mobility in soilNo information available.MobilityNo information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

Australia - EN Page 7/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

ADG Not regulated

IATA Not regulated

Not regulated **IMDG**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

International Inventories

AIIC Listed **NZIoC** Not Listed **ENCS** Not Listed **IECSC** Not Listed **KECL** Not Listed **PICCS** Not Listed

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Australia - EN Page 8/9

DAMPFIX IMMERSED POWDER

Revision Number 2 Supersedes Date: 09-Oct-2016

Revision date 13-Dec-2021

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Dec-2021

Revision Note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

<u>Disclaimer</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Australia - EN Page 9/9