# **SPR ACRYLIC RENDER**





# Section 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product Identifier

Product Name SPR Acrylic Render

Synonyms None

### 1.2 Uses and Uses Advised Against

Use(s) A high strength cement based rendering product. Designed to be mixed with water and

applied onto correctly prepared surfaces

### 1.3 Details of the Supplier and the Product

Supplier Name Novatex Products Pty Ltd

Address 118 Hassall St, Wetherill Park. NSW 2164 Australia

Telephone (02) 97573525

Email <u>info@novatexproducts.com.au</u>
Website <u>www.novatexproducts.com.au</u>

### 1.4 Emergency Telephone Numbers

Emergency 0297573525 (7am to 5pm Monday to Friday EST)

Emergency (A/H) 13 11 26 (Poisons Information Centre)

# Section 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Specific Target Organ Systemic Toxicity (Repeated Exposure): Category 2

Serious Eye Damage / Eye Irritation: Category 2A

Skin Corrosion/Irritation: Category 2

Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

#### 2.2 Label elements

Signal word WARNING

Pictogram(s)





### Hazard statement(s)

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure

### Prevention statement(s)

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment is advised - see first aid instructions.
P362 Take off contaminated clothing and wash before re-use.

Material Safety Data Sheet



Storage statement(s)

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

No information provided.

# Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredients	CAS Number	EC Number	Content
Portland Cement	65997-15-1	266-043-4	20 to 50%
Hydrated Lime	1305-62-0		Up to 5%
Synthetic Additives			5% to 10%
Quartz Sands			50 to 70%
Quartz (Crystalline Silica)	14808-60-7	238-878-4	<1%
Non-hazardous Ingredients	Not Available	Not Available	Remainder

**Ingredient Notes** 

- 1. Depending upon the source material, may contain varying amounts of respirable quartz (crystalline silica).
- 2. Chromium VI is a trace impurity in Portland Cement (< 20 ppm).

# Section 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until

advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running

water. Continue flushing with water until advised to stop by a Poisons Information Centre or a

doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).

If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and safety shower should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

#### 4.3 Immediate medical attention and special treatment needed

Treat as for moderate to strong alkali and symptomatically.

Material Safety Data Sheet



# Section 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2 Special hazards arising from the substance or mixture

Non-flammable. May evolve toxic gases if strongly heated

### 5.3 Advice for firefighters

No fire or explosion hazard exists.

### 5.4 Hazchem code

None allocated.

# Section 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

# 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# Section 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation.

Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

### 7.3 Specific end use(s)

No information provided.



# Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

# **Exposure standards**

Ingredient	Reference	TWA		STE	STEL	
		ppm	mg/m³	ppm	mg/m³	
Portland cement	SWA( AUS)	-	10	-	-	
Quartz (respirable Dust)	SWA (AUS)	-	0.1	-	-	

#### **Biological limits**

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

**PPE** 

**Eye / Face** Wear safety glasses or dust-proof goggles when handling material to avoid contact with eyes.

**Hands** Wear PVC, rubber or cotton gloves when handling material to prevent skin contact.

**Body** Wear long sleeved shirt and full-length trousers.

**Respiratory** Where an inhalation risk exists wear a Class P1 (Particulate) respirator, dependent on a site specific

risk assessment



# Section 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

Appearance	LIGHT GREY POWDER	Solubility (water)	< 10 g/L
Odour	SLIGHT ODOUR	Vapour pressure	NOT AVAILABLE
Flammability	NON FLAMMABLE	Upper explosion limit	NOT RELEVANT
Flash point	NOT RELEVANT	Lower explosion limit	NOT RELEVANT
<b>Boiling point</b>	NOT AVAILABLE	Partition coefficient	NOT AVAILABLE
Melting point	> 1200°C	Auto ignition temperature	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE	Decomposition temperatur	e NOT AVAILABLE
pH	11 to 13	Viscosity	NOT AVAILABLE
Vapour density	NOT AVAILABLE	Explosive properties	NOT AVAILABLE
Specific gravity	1.4 to 1.7 kg/l	Oxidising properties	NOT AVAILABLE
	-	Odour threshold	NOT AVAILABLE

### 9.2 Other information

Density 1400 kg/m³ to 1700 kg/m³ (Bulk)

Material Safety Data Sheet



# Section 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

#### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

#### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

### **10.6 Hazardous decomposition products**

May evolve toxic gases if heated to decomposition.

# Section 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity No known toxicity data is available for this product. Based on available data, the

classification criteria are not met.

**Skin** Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and

dermatitis.

**Eye** Irritating to the eyes. Contact may result in irritation, lacrimation, pain, redness, corneal

burns and possible permanent damage.

**Sensitization** This product is not classified as a skin or respiratory sensitiser. However, some individuals

may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of

chromium.

Mutagenicity Insufficient data available to classify as a mutagen

Carcinogenicity This product contains crystalline silica which is classified as carcinogenic to humans (IARC

Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore, preventing the onset of silicosis will also reduce the cancer risk. Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1), however due to the trace amounts present, the criteria for

classification is not met.

**Reproductive** Insufficient data available to classify as a reproductive toxin.

STOT - single exposure Irritating to the respiratory system. Over exposure may result in irritation of the nose and

throat, coughing. High level exposure may result in breathing difficulties.

STOT – repeated exposure Repeated exposure to respirable silica may result in pulmonary fibrosis Silicosis is a

ibronodular lung disease caused deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of silicosis are coughing and breathlessness. In the wet

state, the likelihood of an inhalation hazard is reduced.

**Aspiration** This product is a solid and aspiration hazards are not expected to occur.

Material Safety Data Sheet



# Section 12. ECOLOGICAL INFORMATION

# 12.1 Toxicity

May be harmful to the aquatic environment due to the alkaline nature of the product. This product is non-toxic to aquatic organisms when present as a cured solid.

# 12.2 Persistence and degradability

Product is persistent and would have a low degradability

### 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

### 12.4 Mobility in soil

A low mobility would be expected in a landfill situation.

### 12.5 Other adverse effects

Avoid contamination of drains and waterways.

# Section 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Waste disposal Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent

dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for

additional information (if required)

**Legislation** Dispose of in accordance with relevant local legislation.

# Section 14. TRANSPORTATION INFORMATION

# NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT	SEA TRANSPORT	AIR TRANSPORT
	(ADG)	(IMDG / IMO	(IATA / ICAO
14.1 UN Number	None Allocated	None Allocated	None Allocated
14.2 Proper	None Allocated	None Allocated	None Allocated
Shipping Name			
14.3 Transport	None Allocated	None Allocated	None Allocated
hazard class			
14.4 Packing Group	None Allocated	None Allocated	None Allocated

# 14.5 Environmental hazards

No information provided

### 14.6 Special precautions for use

Hazchem code None Allocated

Material Safety Data Sheet



# Section 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard

for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

**Labelling of Chemicals** 

Hazard codes Xi Irritant

Xn Harmful

**Risk phrases** R36/37/38 Irritating to eyes, respiratory system and skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

Safety phrases S22 Do not breathe dust.

**S24/25** Avoid contact with skin and eyes.

**S36/37** Wear suitable protective clothing and gloves.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

### Section 16. OTHER INFORMATION

### **Additional information**

### **16.1 PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### **16.2 HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

# 16.3 Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System
EC No. European Community Number
GHS Globally Harmonized System

IARC International Agency for Research on Cancer

**LC50** Lethal Concentration, 50% / Median Lethal Concentration

**LD50** Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

**ppm** Parts Per Million

STEL Short-Term Exposure Limit

STOT RE Specific target organ toxicity (repeated exposure)
STOT SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons SWA Safe Work Australia

TLV Threshold Limit Value
TWA Time Weighted Average

Material Safety Data Sheet



### 16.4 Revision history

Revision	Description
1.0	Initial release 30/9/2019

### 16.5 Report status

This document has been compiled by the manufacturer, importer or supplier of the product and serves as their Material Safety Data Sheet ('MSDS').

The information presented herein is based on data considered to be accurate as of the date of preparation of this MSDS. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorisation given or implied to practice any patented invention without a licence. In addition, no responsibility can be assume by the vendor for any damage or injury resulting from abnormal use, without a risk assessment for safe use, from any failure to adhere to recommended practices or from any hazards inherent in the nature of the products.

This Material Safety Data Sheet (MSDS) applies only to the formulated material as supplied by Novatex Products Cement. It does not apply where the formulation has been altered. In this case a new MSDS may be required to reflect the modified material. Contact Novatex Products for further information.

Printed documents are uncontrolled. Refer to www.novatexproducts.com.au regularly for a more recent copy of the MSDS where it exists.

Prepared by Novatex Products Pty Ltd

118 Hassall St

Wetherill Park. NSW. 2164 Phone +61 (02) 97573525 Fax +61 (02) 97573525

Email <a href="mailto:info@novatexproducts.com.au">info@novatexproducts.com.au</a>
Website: <a href="mailto:www.npvatexproducts.com.au">www.npvatexproducts.com.au</a>

Revision 0
MSDS date: 30th September 2019

**End MSDS**